

SHADES SILVER 20

Performance Data

Total Solar Energy Rejected	77%
Solar Energy Reflected	52%
Solar Energy Absorbed	34%
Solar Energy Transmitted	14%
Visible Light Transmitted	17%
Visible Light Reflected	55%
Ultra Violet Light Rejected	99%
Shading Coefficient	0.27
Solar Heat Gain Coeff. (g Value)	0.23
Emissivity	0.67
Glare Reduction	81%

Performance Guide

Solar Heat Rejection	★ ★ ★ ★ ★
Glare Reduction	★ ★ ★ ★ ★
UV Reduction	★ ★ ★ ★ ★
Fade Reduction	★ ★ ★ ★ ★
Safety & Security	☆ ☆ ☆ ☆ ☆
One-Way Privacy	★ ★ ★ ★ ☆
Two-Way Privacy	☆ ☆ ☆ ☆ ☆
Scratch Coating	Yes
Warranty Period	10 Years

Key: Excellent - ★★★★★ Some Benefit - ★★★☆☆ N/A - ☆☆☆☆☆

Film Notes

Biggest selling solar film with excellent heat and glare rejection.

Gives a building a modern, mirrored finish.

Please refer to your supplier for explanations on performance data, performance guide and application restrictions.

